



Model:	QSQ2w, QSQ2g
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	KM01D
Resolution:	2+2=4MP
Sensor Resolution:	1/2.9" MIS2008*2
Lens:	2*4MM
View angle:	2*80°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point quantity:	6
Video compression standard:	H.265/15FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
Network:	4G or WIFI wireless transmission (support IEEE802.11b/g/n wireless protocol).
Network connection:	4G orWIFI, AP Hotspot, RJ45 Network port
Night vision:	IR-CUT switch Automatic, about 5-8meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision automatically , it can intelligently detected human body, and Turn ON/OFF the White light intelligently)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、 DDNS、 DHCP
Alarm:	①Motion detection and picture push ②AI Human intrusion Detection
ONVIF	ONVIF(option)
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Power input:	12V/2A (not including power supply)
Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH

Quick smart
get smart instantly

