



Model:	QSQ4-W, QSQ4-4G, QSQ4solar
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	KM01N
Resolution:	2+2=4MP
Sensor Resolution:	1/2.9" SC2336*2
Lens:	2*4MM, 10X Optical Zomm
View angle:	2*60° + 1*80°
Pan-tilt:	Rotates Horizontal:355° Vertical : 90°
Preset point quantity:	6
Video compression standard:	H.265/15FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
LED quantity:	Bullet camera: 2pcs Dual Core LED PTZ camera: 4pcs White LED + 5pcs Infrared Led
Network:	WIFI wireless transmission (support IEEE802.11b/g/n wireless protocol).
4G Network :	4G-BAND1/3/5/8/38/39/40/41
Network connection:	4G OR WIFI, AP Hotspot, RJ45 Network port
Night vision:	IR-CUT switch Automatic, about 5-8meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision automatically , it can intelligently detected human body, and Turn ON/OFF the White light intelligently)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、DDNS、DHCP
Alarm:	①Motion detection and picture push ②AI Human intrusion Detection
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)

QuickSmart
get smart instantly

Power input:
Work environment:
Solar panel power:
Battery capacity :

12V/2A (not including power supply)

Working temperature:-10°C ~ + 50°C Working Humidity: ≤95%RH

7,5W

Built-in 8000mah battery

1

2

3