



Model:	QSQ1
APP:	V380 Pro, Yi lot
System structure:	Embedded Linux system, ARM chip structure
Chip:	1/4" SC1346*2
Resolution:	1+1=2MP
Lens	2*3.6MM
Pan-tilt:	Horizontal : 355° Vertical : 90°
Preset point quantity:	6pcs
Video compression standard:	H.264/15FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0 VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation :	Support
Noise reduction:	2D, 3D
Infrared LED:	PT indoor camera: 4pcs infrared LED + 4pcs White LED Bullet camera: 4pcs infrared LED
Network connection:	Support WIFI, AP hotspot (without RJ45 Network port)
Network:	2.4G Wi-Fi (Support IEEE802.11b/g/ N wireless protocol)
Night Version:	Dual Light switch automatic, 5-10 Meters (varies from environment)
Audio:	Built-in microphone and speaker, support two-way real-time audio transmission. ADPCM audio compression standard, self-adaptive
Network protocol:	stream code TCP/IP、UDP、HTTP DDNS、DHCP、FTP、NTP
Alarm:	①Motion detection, picture push ②Human intrusion Detection (optional)
Storage:	TF Card (Max 128G) ; Cloud storage (optional)
Power input:	5V/1.6A (EU and US Plug optional)
Work environment:	Working temperature:-10°C ~ + 50°C Working Humidity: ≤95%RH

Quick smart
get smart instantly